



TDS 9Q10-12/2021

INTERIORS/EXTERIORS

9Q10 SICURO (MATT - SATIN - GLOSSY)

9Q10 SICURO IS A SMOOTH, WATER-BASED, SUPER WHITE ENAMEL, AVAILABLE IN MATT, SATIN AND GLOSSY, WITH SUPER-HIGH OPACITY, ENVIRONMENTALLY FRIENDLY, APPLICABLE BY BRUSH, ROLLER OR SPRAY.



L 2,5



L 1

STABILITY: 2 YEARS
PH: 7 - 9° C
VOC: < 10 GR/L
NOTE *

FEATURES: WASHABLE, SUPER OPAQUE, ODOORLESS
TOOL: BRUSH, ROLLER, SPRAY GUN
DRYING TIME: 8 - 12 HOURS DEPENDING ON THE TEMPERATURE
STORAGE = MAX TEMP. + 30 ° - MIN. TEMP. + 5 °

PHASE 1

APPLY 9Q10 PURAL ACRIL WITH A ROLLER, DILUTED WITH 10% WATER.
LEAVE TO DRY COMPLETELY

PHASE 2

APPLY THE 1ST COAT OF 9Q10 SICURO WITH A ROLLER, DILUTED 5-10% WITH WATER.
LEAVE TO DRY COMPLETELY.

PHASE 3

APPLY THE 2ND COAT OF 9Q10 SICURO WITH A ROLLER, DILUTED 5-10% WITH WATER.

PACKAGE	PACKAGE PERFORMANCE	REFERRING PERFORMANCE
L 2,5	16 - 18 MQ	2 COATS
L 1	6 - 7 MQ	2 COATS
L 9	54 - 63 MQ	2 COATS

HAZARDS IDENTIFICATION
THE PRODUCT IS NOT CLASSIFIED AS DANGEROUS PURSUANT TO THE PROVISIONS OF REGULATION (EC) 1272/2008 (CLP) (AND SUBSEQUENT AMENDMENTS AND ADJUSTMENTS).



*** NOTE**

THE STABILITY PERIOD IS PURELY INDICATIVE, IT REFERS TO THE MINIMUM STABILITY TIME OF THE PRODUCT IF STORED IN GOOD CONDITIONS ACCORDING TO THE INSTRUCTIONS PROVIDED, IN THE ORIGINAL UNOPENED CONTAINERS AND IN SUITABLE TEMPERATURE CONDITIONS. IF STORED PROPERLY, THE PRODUCT MAY HAVE GREATER STABILITY THAN THE MINIMUM RECOMMENDED PERIOD.