



TDS 9Q10-15/2021

INTERIORS/EXTERIORS

9Q10 PURAL ACRIL

9Q10 PURAL ACRIL IS AN ECOLOGICAL WATER-BASED PRIMER FOR INTERIORS AND EXTERIORS SUITABLE FOR PREPARING THE SUBSTRATE BEFORE PAINTING, CREATING THE IDEAL ADHESION FOR SUBSEQUENT LAYERS OF PAINT. HIGHLY CONCENTRATED.



L 2,5



L 1

STABILITY: 2 YEARS
PH: 8 - 11° C
VOC: 15 GR/L
NOTE *

CHARACTERISTICS: SINGLE COAT APPLICATION

TOOL: ROLLER

DRYING TIME: 8 - 12 HOURS DEPENDING ON THE TEMPERATURE

STORAGE = MAX TEMP. + 30 ° - MIN. TEMP. + 5 °

FASE 1

APPLY A COAT OF 9Q10 PURAL ACRIL BY ROLLER
DILUTION: TO BE DILUTED WITH 10% WATER.

PACKAGE	PACKAGE PERFORMANCE*	REFERRING PERFORMANCE
L 2,5	200 - 220 MQ	1 COAT
L 1	80 - 90 MQ	1 COAT

HAZARDS IDENTIFICATION
THE PRODUCT IS NOT CLASSIFIED AS DANGEROUS PURSUANT TO THE PROVISIONS OF REGULATION (EC) 1272/2008 (CLP) (AND SUBSEQUENT AMENDMENTS AND ADJUSTMENTS).



*** NOTE**

THE STABILITY PERIOD IS PURELY INDICATIVE, IT REFERS TO THE MINIMUM STABILITY TIME OF THE PRODUCT IF STORED IN GOOD CONDITIONS ACCORDING TO THE INSTRUCTIONS PROVIDED, IN THE ORIGINAL UNOPENED CONTAINERS AND IN SUITABLE TEMPERATURE CONDITIONS. IF STORED PROPERLY, THE PRODUCT MAY HAVE GREATER STABILITY THAN THE MINIMUM RECOMMENDED PERIOD.